

Rohrdurchmesser d, DN Dichtungseinsatz und Schlüsselweite

Curaflex® A - F

| Rohr-Ø von - bis | DN | Bolzen-Ø | Schlüssel- weite |
|---------------------|-----|----------|---------------------|
| 1 - 12 | 50 | M 5 | 8 |
| 13 - 18 | | | |
| 19 - 24 | | | |
| 1 - 13 | 80 | M 6 | 10 |
| 14 - 21 | | | |
| 22 - 28 | | | |
| 29 - 35 | | | |
| 36 - 40 | | | |
| 41 - 45 | | | |
| 46 - 52 | 100 | M 6 | 10 |
| 53 - 57 | | | |
| 58 - 67 | | | |
| 68 - 77 | 125 | M 6 | 10 |
| 78 - 85 | | | |
| 86 - 94 | 150 | M 6 | 10 |
| 95 - 104 | | | |
| 105 - 115 | | | |
| 116 - 124 | 200 | M 8 | 13 |
| 125 - 135 | | | |
| 136 - 145 | | | |
| 146 - 156 | 250 | M 8 | 13 |
| 157 - 165 | | | |
| 166 - 172 | | | |
| 173 - 179 | | | |
| 180 - 186 | | | |
| 187 - 190 | | | |
| 191 - 197 | 300 | M 8 | 13 |
| 198 - 207 | | | |
| 208 - 215 | | | |
| 216 - 224 | | | |
| 225 - 233 | | | |

| Rohr-Ø von - bis | DN | Bolzen-Ø | Schlüssel- weite |
|---------------------|------|----------|---------------------|
| 234 - 240 | 350 | M 8 | 13 |
| 241 - 249 | | | |
| 250 - 259 | | | |
| 260 - 269 | | | |
| 270 - 278 | | | |
| 279 - 288 | | | |
| 289 - 294 | 400* | M 12 | 19 |
| 295 - 300 | | | |
| 301 - 306 | | | |
| 307 - 311 | | | |
| 312 - 317 | | | |
| 318 - 322 | | M 8 | 13 |
| 323 - 327 | | | |
| 328 - 333 | | | |
| 334 - 339 | 450* | M 12 | 19 |
| 340 - 344 | | | |
| 345 - 350 | | | |
| 351 - 356 | | | |
| 357 - 362 | | | |
| 363 - 368 | | | |
| 369 - 370 | M 8 | 13 | |
| 371 - 375 | | | |
| 376 - 380 | | | |
| 381 - 386 | 500* | M 12 | 19 |
| 387 - 392 | | | |
| 393 - 397 | | | |
| 398 - 403 | | | |
| 404 - 409 | | | |
| 410 - 415 | | | |
| 416 - 420 | M 8 | 13 | |
| 421 - 425 | | | |
| 426 - 430 | | | |

* Zuordnungen gelten nicht für Curaflex® C 40 und A 40.

Maximale Drehmomente

| Bolzen-Ø | Schlüssel- weite | Max. Drehmomente Curaflex® A - F |
|----------|---------------------|-------------------------------------|
| M 5 | 8 | 3 Nm |
| M 6 | 10 | 8 Nm |
| M 8 | 13 | 12 Nm |
| M 10 | 17 | 25 Nm |
| M 12 | 19 | 30 Nm |

| Bolzen-Ø | Schlüssel- weite | Max. Drehmomente Curaflex® A 40/C 40 |
|----------|---------------------|---|
| M 5 | 8 | 2 Nm |
| M 6 | 10 | 5 Nm |
| M 8 | 13 | 7 Nm |
| M 10 | 17 | 15 Nm |
| M 12 | 19 | 18 Nm |

